

## Technical Specifications

### Mechanical

<b>Dimensions</b>	Device: Ø62 x 54 mm (Ø2.5 x 2.1") In-wall mount: Ø89 x 63.1 mm (Ø3.5 x 2.5") On-wall Mount: Ø62 x 20.2 mm (Ø2.5 x 0.8")
<b>Weight</b>	Device: 158 g (5.6 oz) In-wall mount: 91 g (3.2 oz) On-wall mount: 28 g (1 oz)
<b>Enclosure material</b>	Polycarbonate, aluminum alloy
<b>Mount material</b>	Polycarbonate, zinc alloy

### System

<b>Networking interface</b>	10/100 MbE port
<b>Power method</b>	PoE
<b>Supported voltage range</b>	44—57V DC
<b>Max. power consumption</b>	3W
<b>ESD/EMP protection</b>	Air: ± 8kV, contact: ± 4kV
<b>LED</b>	R/G/B/W
<b>Button</b>	Factory reset
<b>Ambient operating temperature</b>	0 to 40° C (32 to 104° F)
<b>Ambient operating humidity</b>	10 to 90% noncondensing
<b>Certifications</b>	CE, FCC, IC

### Audio

<b>Speaker</b>	Yes
<b>Buzzer</b>	Yes

### Software

<b>Web application</b>	UniFi Protect UniFi Access
<b>Mobile app</b>	UniFi Protect iOS™ and Android™