

Mechanical

| | |
|---------------------------|-------------------------------------|
| Dimensions | 130 x 55 x 34 mm (5.1 x 2.2 x 1.3") |
| Weight | 200 g (7.1 oz) |
| Enclosure material | Polycarbonate |
| Mount material | Polycarbonate |

Hardware

| | |
|--------------------------------------|--|
| Management interface | WiFi |
| Networking interface | (1) GbE RJ45 port |
| PoE interface | (1) Passive PoE output |
| Button | (1) Factory-reset |
| LED | (4) Blue: signal (1) White/blue: indicator |
| Power method | 100—240V AC, 0.45A Max., 50/60 Hz |
| Max. power consumption | AC input: 25W Excluding PoE output: 10W |
| Max. PoE wattage per port | 15W |
| Supported voltage range | 100—240V AC |
| WiFi standards | 802.11a/n/ac |
| Max. TX power | |
| 2.4 GHz | — |
| 5 GHz | 21 dBm |
| 6 GHz | — |
| MIMO | |
| 2.4 GHz | — |
| 5 GHz | 2 x 2 |
| 6 GHz | — |
| Max. data rate | |
| 2.4 GHz | — |
| 5 GHz | 866.7 Mbps (BW80) |
| 6 GHz | — |
| Antenna gain | |
| 2.4 GHz | — |
| 5 GHz | Internal antenna : 5 dBi / External omni antenna : 4 dBi |
| 6 GHz | — |
| Antenna | (1) Internal antenna (1) RP-SMA connector for external omni-antenna |
| Mounting | Wall (Included) |
| Ambient operating temperature | -10 to 40° C (14 to 104° F) |
| Ambient operating humidity | 5 to 95% noncondensing |
| Certifications | CE, FCC, IC |
| Supported Data Rates | |
| 802.11a | 6, 9, 12, 18, 24, 36, 48, 54 Mbps |
| 802.11n | 6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40) |
| 802.11ac | 6.5 Mbps to 866.7 Gbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80) |